

פתרונות הוידאו VUPoint

קטלוג מוצרים



החדשה VUpoint NVR היא מערכת הקלטה Plug & Play, משלבת יכולות אימות אזעקה מתקדמות, המספקות פתרון וידאו מלא וייחודי של מערכת הקלטה NVR ומצלמות IP. מתקין מערכות אזעקה ווידאו? הפתרון המשולב והייחודי של RISCO היא הבחירה הטובה ביותר עבורך.



RISCO Cloud

גיבוי אירועים, ניהול מערכת הקלטה מרחוק בממשק מתקין בענן ואבטחת סייבר מתקדמת.



אפליקציה אחת. פתרון מושלם.

אינטגרציה עם מערכות האבטחה המקצועיות של RISCO, המספקות אימות אזעקה בזמן אמת, צפייה בוידאו חי והקלטה, הכל באפליקציה אחת!



פתרון וידאו מלא P2P





מגוון מערכות הקלטה NVR ומצלמות IP כפתרון לכל התקנה וצורך.

VUpoint P2P

	PoE Technology			
	VUpoint P2P Cube IP Camera	VUpoint P2P Dome IP Camera	VUpoint P2P Bullet IP Camera	VUpoint P2P Eyeball IP Camera
				
Image Sensor	1/3" 1.3MP CMOS	1/2.9" 2MP CMOS	1/2.8" 2MP STARVIST™ CMOS	1/2.8" 2MP STARVIST™ CMOS
Lens	2.8 mm/F2.2	3.6 mm/F2.0	3.6mm/F1.6	3.6mm/F1.6
FDV-H	92°	83°	87°	87°
Day/Night	ICR	ICR	ICR	ICR
WDR		DWDR	128dB	128dB
Max IR Distance	10m	30m	40m	50m
Video Compression	H.264	H.265+/H.265 H.264+/H.264	H.264+/H.264 H.265+/H.265	H.265+/H.265 H.264+/H.264
Max Resolution	1.3M (1280×960)	1080P (1920×1080)	1080P (1920×1080)	1080P (1920×1080)
Frame Rate	30fps@1.3MP	30fps@1080P	60fps@1080P	60fps@1080P
Multi-Streaming	2 streams	2 streams	3 streams	3 streams
Pan/Tilt	-	-	-	-
WiFi	-	-	-	-
Audio In/Out	Built-in Mic & Speaker			Built-in Mic
Memory Slot	Micro SD, Max. 128GB	Micro SD, Max. 128GB	Micro SD, Max. 128GB	Micro SD, Max. 128GB
Alarm In/Out	1 in/1 out			
Ingress Protection		IP67	IP67	IP67
Working Temperature	-10°C ~ +45°C	-30°C~+60°C	-30°C~+60°C	-30°C~+60°C
Power	DC12V PoE (802.3af) (Class 0) Max. 5W	DC12V PoE (802.3af) (Class 0) Max. 4.6W	DC12V PoE (802.3af) (Class 0) Max. 6W	DC12V PoE (802.3af) (Class 0) Max. 5.5W
Model	RVCM11W	RVCM32P1	RVCM52P11	RVCM72P12

	Wi-Fi Technology			
VUpoint P2P Bullet Varifocal IP Camera	VUpoint P2P Pan/Tilt IP Camera	VUpoint P2P Cube IP Camera	VUpoint P2P Dome IP Camera	VUpoint P2P Bullet Outdoor IP Camera
				
1/2.7" 2Mp CMOS	1/3" 1.3MP CMOS	1/3" 1.3MP CMOS	1/3" 1.3MP CMOS	1/3" 1.3MP CMOS
2.7~12mm/F1.4 Motorized	3.6 mm/F2.0	2.8 mm/F2.0	2.8 mm/F2.5	2.8 mm/F2.0
99°~ 37°	72.2°	95°	92°	92°
ICR	ICR	ICR	ICR	ICR
128dB				
60m	10m	10m	30m	30m
H.264+/H.264	H.264	H.264	H.264	H.264
1080P (1920×1080)	1.3M (1280×960)	1.3M (1280×960)	1.3M (1280×960)	1.3M (1280×960)
60fps@1080P	30fps@1.3MP	30fps@1.3MP	30fps@1.3MP	30fps@1.3MP
3 streams	2 streams	2 streams	2 streams	3 streams
-	√	-	-	-
-	√	√	√	√
	Built-in Mic & Speaker	Built-in Mic & Speaker		
Micro SD, Max. 128GB	Micro SD, Max. 128GB	Micro SD, Max. 128GB	Micro SD, Max. 128GB	Micro SD, Max. 128GB
		1 in/1 out		
IP67			IP67	IP67
-30°C~+60°C	-10°C ~ +45°C	-10°C ~ +45°C	-10°C ~ +50°C	-10°C ~ +50°C
DC12V PoE (802.3af) (Class 0) Max. 12.95W	DC5V 2A Max. 12.95W	DC12V Max. 3W	DC12V Max. 4.6W	DC12V Max. 4.6W
RVCM52P13	RVCM61H03	RVCM11W	RVCM32W02	RVCM52W01

VUpoint NVR

	4ch NVR	4ch PoE NVR	8ch PoE NVR	16ch NVR
				
System				
Audio and Video				
IP Camera Input	4 Channel	4 Channel	8 Channel	16 Channel
Two-way Talk	1 Channel Input, 1 Channel Output, RCA			
Display				
Interface	1 HDMI, 1 VGA			
Recording				
Compression	H.264/H.265			
Resolution	8Mp/ 6Mp/ 5MP/ 4MP/1080P/ 1.3MP/ 720P etc.			
Record Rate	80Mbps			
Bit Rate	16Kbps ~ 20Mbps Per Channel			
Record Mode	Continuous, Motion			
Network				
Interface	1 RJ-45 Port (10/100Mbps)			
PoE		4	8	
Storage				
Internal HDD	1 SATA III Port, Up to 6 TB capacity			
Electrical				
Power Supply	12V, 2A	48V, 1.5 A	48V/53V, 2A/1.8A	12V, 2A
Power Consumption	NVR: <7.5W (Without HDD)	NVR: <7.5W (Without HDD) PoE: Max 25.5w for single port, 50w in total	NVR: <8.3W (Without HDD) PoE: Max 25.5w for single port, 80w in total	NVR: <7.5W (Without HDD)
Environmental				
Operating Conditions	-10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa			
Storage Construction	-20°C ~ +70°C (-4°F ~ +158°F), 0 ~ 90% RH			
Dimensions:	Smart 1U, 204.6mm×204.6mm ×45.6mm (8.1" x 8.1" x 1.8")	Smart 1U, 204.6mm×204.6mm ×45.6mm (8.1" x 8.1" x 1.8")	Smart 1U, 270mm×204.7mm ×45.7mm (10.6" x 8.1" x 1.8")	Smart 1U, 204.6mm×204.6mm ×45.6mm (8.1" x 8.1" x 1.8")
Net Weight:	0.45kg (0.99 lb) (without HDD)	0.45kg (0.99 lb) (without HDD)	0.65kg (1.43 lb) (without HDD)	0.45kg (0.99 lb) (without HDD)
Certifications				
CE	EN55032, EN55024, EN50130-4, EN60950-1			
FCC	Part 15 Subpart B			
RCM	EN55032, EN55024, EN50130-4, IEC 60950-1			
Model	RVNVR040020	RVNVR04002P	RVNVR08002	RVNVR16002